

POWER RACK

WLX3600

cod. WLX-3600


TRALICCIO TRAZIONI
MULTIPRESA

TRUSS WITH MULTIPLE HANDLES



cod. LAT-ATTWLX-3600

OPTIONAL
LAT/ PULLDOWN/
SEATED ROW MACHINE



RACKS

BILANCIERI Altezza j-cup regolabile (450-1890 mm) su 25 livelli.
Interasse 60 mm J-cup spessore 6 mm con protezione UHMW
DIMENSIONI PRODOTTO: 1463x1210x2322 mm
PESO MAX STRUTTURA 300 Kg
PESO: 132 kg
CLASSE D'UTILIZZO PROFESSIONALE (EN20957-1 / EN957-4 classe S)

BARBELLS J-cup height adjustable (450-1890 mm) on 25 levels.
Distance 60 mm J-cup 6 mm thickness with UHMW protection pads
SET UP SIZE 1463x1210x2322 mm
MAX STRUCTURE WEIGHT 300 kg
WEIGHT: 132 kg
COMMERCIAL USE (EN20957-1 / EN957-4 class S)

- Struttura tubolare in acciaio rinforzato a sezione 75x75 mm - spessore 3 mm
- Verniciatura doppia a polveri epossidiche, antigraffio .
- Dotazione: 2 j-cups, 2 safety bars, traliccio trazioni

- Structure square heavyduty steel tubing 75x75 mm - thickness 3 mm
- Painting double heavy duty powder coating painting, scratch-resistant
- Equipment: 2 j-cups, 2 safety bars, truss with multiple-handle.

LAT/ PULLDOWN/ SEATED ROW MACHINE **OPTIONAL**.

- Peso max caricabile 160 kg.
- Caricamento a dischi con foro $\varnothing$ 25 mm e $\varnothing$ 50 mm.
- Sistema di carrucole /puleggie con cuscinetti a sfera.
- Dotazioni/note: lat bar, barra tricipiti, poggia piedi per seated row, adattatore per utilizzo dischi in ghisa con foro $\varnothing$ 50 mm inclusi.

- Max loadable weight 160 Kg.
- For weight plates with 25 mm and 50 mm diameter hole.
- Pulleys system with ball bearings.
- Equipment/note: lat bar, triceps bar, foot supports for seated row, adapter for weight plates with 50 mm diameter hole included.

