


ALL IN ONE

ASX4500

cod. ASX-4500



MUSCOLI COINVOLTI MUSCLE GROUPS

■ Full body

OPTIONAL



COD. J-ARMSASX4500
Jammer arms



COD. LAT-SEATASX-4.5-6
Lat seat



COD. LEG-PRESSASX
Leg press



COD. W-HOLDERASX
Perno porta pesi
Weight plates holder



COD. M-BARASX
Multifunctional bar




COD. LPDASX-4.5-6
Lat pull down



COD. MLIFTASX-4.5-6
Monolift



COD. LP-SUPPORTASX4500
Supporto leg press
Leg press support



STRENGTH - ALL IN ONE

PULLEY regolabile 321-1822 mm su 31 livelli interasse 50 mm
PACCO PESI in acciaio 2x90kg
J-CUP/SAFETY SPOTTER ARMS Extra strong spessore 5 mm con protezione UHMW (Ultra High Molecular Weight). Regolabile 321-1822 mm su 31 livelli interasse 50 mm
DIMENSIONI PRODOTTO: 2035x1730x2130 mm
PESO MASSIMO UTILIZZATORE 135 Kg
PESO: 363.2 kg
CLASSE D'UTILIZZO PROFESSIONALE (EN20957-1 / EN957-2 / EN957-4 classe S)

PULLEYS adjustable on 31 levels (321-1822 mm) distance 50 mm
WEIGHT STACK steel weight stack 2x90 kg
J-CUP/SAFETY SPOTTER ARMS Extra strong - 5 mm thickness with UHMW (Ultra High Molecular Weight) protection pads, adjustable on 31 levels (321-1822 mm) distance 50 mm
SET UP SIZE 2035x1730x2130 mm
MAX USER WEIGHT 135 Kg
WEIGHT: 363.2 kg
COMMERCIAL USE (EN20957-1 / EN957-2 / EN957-4 class S)

- Struttura a sezione rettangolare 50x70 mm - spessore 2,5 mm
- Ratio: 2:1 / fly handle - 2:1 / lat pull down - 2:1 / seated rowing
- Bilanciere: 2037 mm, scorrimento su cuscinetti a sfera lineari, 2 sicurezze con gancio regolabile, regolabili su 11 posizioni (353-1822 mm), passo 130 mm. Diametro porta dischi da 50 mm
- DOTAZIONI/NOTE 3-IN-1 dual pulley, smith machine, rack. 2 J-hook, coppia fermi di sicurezza bilanciere, barra trazioni, parallele, porta bilanciere, 6 porta dischi ø50 mm e 25 mm, 8 ferma dischi a molla ø49 mm. Attachments: cavigliera, corda doppia tricipiti, catena, landmine, 2 maniglie trazioni, pedana per low row, maniglia doppia, barra tricipiti, bilanciere e bilanciere CURL.

- Structure rectangular tubing 50x70 mm - thickness 2,5 mm
- Ratio: 2:1 / fly handle - 2:1 / lat pull down - 2:1 / seated rowing
- Barbell: 2037 mm, linear bearings sliding, 2 safety systems with hook to avoid barbell falling, vertically adjustable on 11 levels (353-1822 mm), distance 130 mm. Weight plate holder diameter suitable for ø50 mm weight plates
- EQUIPMENT/NOTES 3-IN-1 dual pulley, smith machine, rack. 2 J-hooks, 2 safety spotter arms, chin-up bar, dip up bar, barbell storage, 6 weight plates holders for ø50 mm and 25 mm plates, 8 olympic spring clips ø49 mm. Attachments : ankle strap, rope, chain, landmine, non-slip metal footplate, 2 Y- handles, V-bar, short straight bar, straight bar and curved bar.



TABELLA COMPARATIVA
COMPARATIVE CHART

