

ALL IN ONE

ASX5000

cod. ASX-5000

OPTIONAL



COD. J-ARMSASX2-4-5
Jammer arms



COD. LAT-SEATASX2-4-5
Lat seat



COD. LEG-PRESSASX
Leg press




COD. W-HOLDERASX
Perno porta pesi
Weight plates holder



COD. M-BARASX
Multifunctional bar




COD. LPDASX-2-4-5
Lat pull down



MUSCOLI COINVOLTI MUSCLE GROUPS

■ Full body



STRENGTH - ALL IN ONE

PULLEY regolabile 266x1841 mm su 22 livelli interasse 75 mm
PACCO PESI in acciaio 2x90kg
J-CUP/SAFETY SPOTTER ARMS Extra strong spessore 5 mm con protezione UHMW (Ultra High Molecular Weight). Regolabile 316-1816 mm su 31 livelli interasse 50 mm
DIMENSIONI PRODOTTO: 1944x1670x2170 mm
PESO MASSIMO UTILIZZATORE 135 Kg
PESO: 391.5 kg
CLASSE D'UTILIZZO PROFESSIONALE (EN20957-1 / EN957-2 / EN957-4 classe S)

PULLEYS adjustable on 22 levels (266x1841 mm) distance 75 mm
WEIGHT STACK steel weight stack 2x90 kg
J-CUP/SAFETY SPOTTER ARMS Extra strong - 5 mm thickness with UHMW (Ultra High Molecular Weight) protection pads, adjustable on 31 levels (316-1816 mm) distance 50 mm
SET UP SIZE 1944x1670x2170 mm
MAX USER WEIGHT 135 Kg
WEIGHT: 391.5 kg
COMMERCIAL USE (EN20957-1 / EN957-2 / EN957-4 class S)

- Struttura tubolare a sezione rettangolare 50x70 mm - spessore 2,5 mm/2 mm e quadrata 50x50 mm - spessore 2 mm
- Ratio: 2:1 / smith bar - 2:1 / fly handle - 2:1 / lat pull down - 2:1 / seated rowing
- Bilanciere: 1944mm, scorrimento su cuscinetti a sfera lineari, 2 sicurezze con gancio regolabile, regolabili su 11 posizioni (539 - 1861 mm), passo 150 mm. Diametro porta dischi da 50 mm. Sistema brevettato di aggancio bilanciere guidato ai pacchi peso
- DOTAZIONI/NOTE 3-IN-1 dual pulley, smith machine, rack, 2 J-hook, coppia fermi di sicurezza bilanciere con rulli gambe in foam, barra trazioni multi presa, parallele, porta bilanciere, 4 porta dischi ø50 mm, 4 ferma dischi a molla ø49 mm, 2 ferma dischi a molla ø47 mm. Attachments : cavigliera, corda doppia tricipiti, catena, landmine, 2 maniglie trazioni con catena regolabile, maniglia doppia, barra tricipiti, bilanciere e bilanciere CURL, pedana per low row.

- Structure section rectangular tubing 50x70 mm - thickness 2,5 mm/2 mm and square tubing 50x50 mm - thickness 2 mm
- Ratio: 2:1 / smith bar - 2:1 / fly handle - 2:1 / lat pull down - 2:1 / seated rowing
- Barbell: 1944mm, linear bearings sliding, 2 safety systems with hook to avoid barbell falling, vertically adjustable on 11 levels (539 - 1861 mm), distance 150 mm. Weight plate holder diameter suitable for ø50 mm weight plates. Patented system to link the barbell to the weight stacks
- EQUIPMENT/NOTES 3-IN-1 dual pulley, smith machine, rack, 2 J-hook, set leg holder foam, multi-grip chin-up bar, dip up bar, barbell storage, 4 weight plates holders for ø50 mm plates, 4 olympic spring clips ø49 mm, 2 spring clips ø47 mm. Attachments : ankle strap, rope, chain, landmine, 2 Y- handles with adjustable chan, V-bar, short straight bar, straight bar and curved bar, non-slip metal footplate.



TABELLA COMPARATIVA
COMPARATIVE CHART